Printing date 16.07.2002

Reviewed on 01.07.2002

1 Identification of the substance/preparation and of the company/undertaking

· Product details

*

· Trade name: FUJI LINING LC - LIQUID

· Application of the substance / the preparation Auxiliary for dental technology

• Manufacturer/Supplier: GC EUROPE N.V. Interleuvenlaan 13 B-3001 Leuven

+32/(0)16/39.80.50

· Further information obtainable from: Technical Operations

2 Composition/information on ingredients

· Chemical characterization

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 868-77-9	2-hydroxyethyl methacrylate	🗙 Xi; R 36/38-43	25-50%	
EINECS: 212-782-2	Glycol methacrylate	_		
CAS: 90030-10-4	Polyacrylic acid	🗙 Xi; R 38	25-50%	
	Triethylene glycol Dimethacrylate	🗙 Xi; R 36/38-43	5-10%	

3 Hazards identification

· Hazard description:



Xi Irritant

• *Information concerning particular hazards for human and environment: R 36/38 Irritating to eyes and skin.*

R 43 May cause sensitisation by skin contact.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- Immediately rinse with water.
- · After eye contact:
- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.* • *After swallowing:* If symptoms persist consult doctor.

5 Fire-fighting measures

• Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 2)

Material Safety Data Sheet According to 91/155 EC

Printing date 16.07.2002

Reviewed on 01.07.2002

Trade name: FUJI LINING LC - LIQUID

(Contd. of page 1)

· Protective equipment: No special measures required.

6 Accidental release measures

· Person-related safety precautions: Not required.

- Measures for environmental protection: Do not allow to enter sewers/surface or ground water.
- Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

- · Handling:
- · Information for safe handling: No special measures required.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- *Further information about storage conditions: Keep receptacle tightly sealed.*

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin. • **Respiratory protection:**

In case of exposure to dust over regulatory limits wear a personal repirator of an approved type (P2).

• Protection of hands:



Protective gloves

• Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

• General Information

Form:

Liquid

(Contd. on page 3)

Printing date 16.07.2002

Reviewed on 01.07.2002

Trade name: FUJI LINING LC - LIQUID

		(Contd. of page 2
Colour:	Light yellow	
Odour:	Odourless	
• Change in condition Melting point/Melting range: Boiling point/Boiling range:		
· Flash point:	97°C	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Density:	Not determined.	
• Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Solvent content: Organic solvents:	0.0 %	
· Solids content:	55.0 %	

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Acute toxicity:

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant.

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 4)

GB

Material Safety Data Sheet According to 91/155 EC

Printing date 16.07.2002

Reviewed on 01.07.2002

Trade name: FUJI LINING LC - LIQUID

(Contd. of page 3)

GB

• Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14 Transport information

· Land transport ADR/RID (cross-border) · ADR/RID class: -

· Maritime transport IMDG:

• Marine pollutant: No

15 Regulatory information

\cdot Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

• Code letter and hazard designation of product: Xi Irritant

· Risk phrases:

36/38 Irritating to eyes and skin.43 May cause sensitisation by skin contact.

· Safety phrases:

- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 28 After contact with skin, wash immediately with plenty of water.

· National regulations:

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

· Relevant R-phrases

36/38 Irritating to eyes and skin.

- *38 Irritating to skin.*
- 43 May cause sensitisation by skin contact.
- · Department issuing MSDS: Technical Operations
- · Contact: Dr. J.A. Yearn
- * Data compared to the previous version altered.

95-100%

Printing date 16.07.2002

Reviewed on 01.07.2002

1 Identification of the substance/preparation and of the company/undertaking

· Product details

• Trade name: FUJI LINING LC - POWDER

· Application of the substance / the preparation Auxiliary for dental technology

• Manufacturer/Supplier: GC EUROPE N.V. Interleuvenlaan 13 B-3001 Leuven +32/(0)16/39.80.50

· Further information obtainable from: Technical Operations

2 Composition/information on ingredients

· Chemical characterization

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Alumino-Silicate Glass

3 Hazards identification

• *Information concerning particular hazards for human and environment: Not applicable.* • *Classification system:*

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

· General information: No special measures required.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

· Suitable extinguishing agents:

- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Protective equipment: No special measures required.

6 Accidental release measures

• Person-related safety precautions: Not required.

- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- *Measures for cleaning/collecting: Pick up mechanically.*
- · Additional information: No dangerous substances are released.

7 Handling and storage

· Handling:

- · Information for safe handling: No special measures required.
- · Information about fire and explosion protection: No special measures required.

(Contd. on page 2)

GB

Printing date 16.07.2002

Reviewed on 01.07.2002

Trade name: FUJI LINING LC - POWDER

(Contd. of page 1)

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · Class according to regulation on flammable liquids: Void

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.

• Respiratory protection:

- In case of exposure to dust over regulatory limits wear a personal repirator of an approved type (P2).
- **Protection of hands:** Not required.
- Eye protection: Not required.

Physical and chemical properties		
· General Information		
Form:	Solid	
Colour:	White	
Odour:	Odourless	
· Change in condition		
Melting point/Melting range: Undetermined.		
Boiling point/Boiling range:	Undetermined.	
· Flash point:	Not applicable.	
· Self-igniting:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
· Density:	Not determined.	
· Solubility in / Miscibility with		
water:	Insoluble.	
· Solvent content:		
Organic solvents:	0.0 %	
· Solids content:	100.0 %	

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.

(Contd. on page 3)

<u>в</u>с э) — GB · Dangerous decomposition products: No dangerous decomposition products known.

Printing date 16.07.2002

Reviewed on 01.07.2002

Trade name: FUJI LINING LC - POWDER

(Contd. of page 2)

GB

11 Toxicological information

• Acute toxicity:

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· Product:

· Recommendation Smaller quantities can be disposed of with household waste.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID (cross-border) · ADR/RID class: -
- · Maritime transport IMDG:
- Marine pollutant: No

15 Regulatory information

• Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals. The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

· National regulations:

· Classification according to VbF: Void

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

· Department issuing MSDS: Technical Operations

- · Contact: Dr. J.A. Yearn
- * Data compared to the previous version altered.