

Page 1/10

Tel.: +49 (0)800 4372522

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
 - · Trade name: iBOND Total Etch
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Dental bonding material
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Informing department: E-Mail: msds@kulzer-dental.com

· 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

glutaral

4-methacryloxyethyltrimellitic acid anhydride

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

Trade name: iBOND Total Etch

· Precautionary statements

(Contd. of page 1)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

· 2.3 Other hazards -

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: -

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 2119457610-43-xxxx	ethanol Flam. Liq. 2, H225	25-50%
CAS: 868-77-9 EINECS: 212-782-2	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
	Poly(methacrylic-oligo-acrylic acid) Eye Irrit. 2, H319	0-5%
CAS: 70293-55-9	4-methacryloxyethyltrimellitic acid anhydride Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0-5%
CAS: 111-30-8 EINECS: 203-856-5	glutaral Acute Tox. 3, H301; Acute Tox. 3, H331; Resp. Sens. 1, H334; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Skin Sens. 1, H317	0-5%
CAS: 72869-86-4 EINECS: 276-957-5	diurethandimethacrylate Aquatic Chronic 3, H412	0-5%

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact Instantly wash with water and soap and rinse thoroughly.
 - · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
 - · After swallowing

Rinse out mouth and then drink plenty of water.

Instantly call for doctor.

In case of persistent symptoms consult doctor.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus.

· Additional information -

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

No special measures required.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Send for recovery or disposal in suitable containers.

· 6.4 Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store cool (not above 25 °C).

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Printing date 03.06.2017 Revision: 03.06.2017

Trade name: iBOND Total Etch

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:
64-17-5 ethanol
WEL Long-term value: 1920 mg/m³, 1000 ppm
111-30-8 glutaral
WEL Short-term value: 0.2 mg/m³, 0.05 ppm Long-term value: 0.2 mg/m³, 0.05 ppm

· DNELs

64-17-5 ethanol

Orai	ge.pop., I.te, syst.	87 mg/Kg (na)
Dermal	worker profess., I.te., syst.	343 mg/Kg/d (nd)
	ge.pop., acu., local	950 mg/Kg/d (nd)
	ge.pop., l.te, syst.	206 mg/Kg/d (nd)
Inhalative	worker profess., acute, local	1900 mg/m3 (nd)
	worker profess., I.te., syst.	1900 mg/m3 (nd)
	ge.pop., acu., local	950 mg/m3 (nd)
	ge.pop., l.te, syst.	114 mg/m3 (nd)

· PNECs

64-17-5 ethanol

freshwater	0.96 mg/l (nd)
marine water	0.79 mg/l (nd)
STP	580 mg/l (nd)
sedim., dw, fre.wat.	3.6 mg/Kg (nd)
freshwater marine water STP sedim., dw, fre.wat. soil,dw	0.63 mg/Kg (nd)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Breathing equipment: Breathing protection recommended.
- · Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 4)

Check protective gloves prior to each use for their proper condition. recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

· Steam pressure at 20 °C:

· Relative density

· Density

· Eye protection: not absolutely neccessary

· Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and • General Information	chemical properties
· Appearance: · Form:	Fluid
· Colour:	Yellowish
· Smell:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined Not determined
· Flash point:	24 °C
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	<i>4</i> 25 ℃
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· Critical values for explosion:	
· Lower:	3.5 Vol %
· Upper:	15.0 Vol %

57 hPa

Not determined

Not determined.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Printing date 03.06.2017 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 5)

· Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· dynamic: Not determined. · kinematic: Not determined.

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information: -

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
 - · Acute toxicity Based on available data, the classification criteria are not met.

· LD	/LC50 valu	les that are relevant for classification:
64-17-5 e	ethanol	
Oral	LD50	6200 mg/kg (rat)
Inhalative	LC50/4 h	95.6 mg/l (rat)
41137-60)-4 diuretha	andimethacrylate
Oral	LD50	>5000 mg/kg (rat)
868-77-9	2-hydroxy	ethyl methacrylate
Oral	LD50	5564 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (can)
Poly(me	thacrylic-o	ligo-acrylic acid)
Oral	LD50	>5000 mg/kg (rat)
70293-55	5-9 4-metha	acryloxyethyltrimellitic acid anhydride
Oral	LD50	> 2000 mg/kg (mouse)
Dermal	LD50	> 2000 mg/kg (mouse)
72869-86	3-4 diuretha	andimethacrylate
Oral	LD50	>5000 mg/kg (rat)
		(Contd. on pag



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 6)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
 - · Aquatic toxicity:

868-77-9 2-hydroxyethyl methacrylate

LC50/96h 227 mg/l (fish)

72869-86-4 diurethandimethacrylate

LC50/96h 10.1 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
 - Additional ecological information:
 - · General notes: Avoid transfer into the environment.
- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

18 01 06 | chemicals consisting of or containing dangerous substances

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2017 Version number 3 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 7)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1170
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1170 ETHANOL SOLUTION ETHANOL (ETHYL ALCOHOL) Ethanol
· 14.3 Transport hazard class(es)	Lulanoi
· ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-D A
· 14.7 Transport in bulk according to Annex Marpol and the IBC Code	x II of Not applicable.
· Transport/Additional information:	-
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packagii 30 ml
	30 ml (Contd. on page 1



Page 9/10

(Contd. of page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Revision: 03.06.2017 Printing date 03.06.2017

Trade name: iBOND Total Etch

· IMDG

· Transport category

· Tunnel restriction code

Maximum net quantity per outer packaging: 1000 ml 3 D/E 5L

· Limited quantities (LQ) Code: E1 Excepted quantities (EQ)

Maximum net quantity per inner packaging:

30 ml Maximum net quantity per outer packaging: 1000 ml

UN1170, ETHANOL (ETHYL ALCOHOL), 3, III · UN "Model Regulation":

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent. Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Printing date 03.06.2017 Revision: 03.06.2017

Trade name: iBOND Total Etch

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
** Data compared to the previous version altered.

* Data compared to the previous version altered.